



# ENDRESS

## Power Generators

### EFA 850 S4 320 ST

Order No. **716277**

#### Main features

Light output [W]	1280
Light source / lamps	LED 4 × 320 W
Mast	340° drehbar

#### Operation

Trailer drawbar	starr / kurze Deichsel
Inertial brake	ja
Lifting system	Hydraulisch
Max. light spot height (m)	8,5
Min. transport height (m)	2,4
Dimensions L x W x H [mm]	2200 x 1400 x 2440
Weight in kg ca.	980
Illumination range (5 lux min.) [m <sup>2</sup> ]	4500
Light flux (Lumens) approx. [lm]	167300
Mains supply socket	1x CEE 230 V / 16 A
Running time (hours)	181,8

#### Chassis

Permissible total weight [kg]	1300
Permissible trailer nose weight [kg]	100

#### Generator recommendation

Insulation class	23
Nominal voltage [V]	230
Nominal current 3~ (PRP) [A]	16

garantía alguna ni implícita ni expresa del rendimiento de un motor concreto.

Technical data and illustrations are not binding. We assume no liability for misprints.

2021-7-8

**ENDRESS Elektrogerätebau GmbH**  
Neckartenzlinger Str. 39  
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0  
Fax.: +49 (0) 7123-9737-50  
www.endress-generators.de



EFA 850 S4 320 ST

Order No. 716277



**Power Generators**

Engine	
Brand	Kubota
Model	Z482
Cooling system	Wassergekühlt
Engine output (PRP) [kW]	3,5
RPM [U/min]	1500
Fuel	Diesel
Fuel tank capacity [l]	100
Fuel consumption @ 75% PRP [L/h]	0,55
Running time @ 75% PRP	181,8
Sound power level LWA [db(A)]	83
Sound pressure level LPA (7 m) [db(A)]	58
Shockproof sockets	1x CEE 230 V / 16 A

Equipment features	
Simple accessibility through three maintenance doors	
Super sound proofed - 58 dB(A) at 7m	
Simple and rapidly adjustable parking stand	
Spirit level - for simple alignment	
Simple to operate control unit - all functions can be actuated over a control panel	
LED spotlights powered from a 48 V power source for your safety	
Central crane loading lug	
Forklift pockets integrated	
A compact design	
Twilight sensor and digital timer installed as standard	

Accessories	Order No.
DIN drawbar eye 50mm	341 505
Preheating System	<b>341 508</b>
Insulation Monitoring	<b>341 509</b>

garantía alguna ni implícita ni expresa del rendimiento de un motor concreto.

Technical data and illustrations are not binding. We assume no liability for misprints.

2021-7-8

**ENDRESS Elektrogerätebau GmbH**  
Neckartenzlinger Str. 39  
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0  
Fax.: +49 (0) 7123-9737-50  
www.endress-generators.de

